



Knowledge for Tomorrow

ECSS Training Session – 04.04.2022 - online

ECSS-U-ST-20C (1 August 2019) Space sustainability

Planetary Protection









Agenda

- Introduction to Planetary Protection, ECSS-U-ST-20C- 1h Silvio Sinibaldi (ESA)
- Basic of Microbiology, bioburden assessment and bioburden reduction- 1h Petra Rettberg (DLR)
- Planetary Protection and contamination control- 1h
 Delphine Faye (CNES)
- Implementation of Planetary Protection Requirements –Case study ExoMars-1.5h
 Diana Margheritis (TASI)







Trainer's information: Diana B. Margheritis

-Thales Alenia Space Italy, Turin, Domain Exploration & Science group

- Licentiate in Chemistry from National University of Buenos Aires (UNBA) Argentina
- Planetary Protection Manager and Cleanliness& Contamination Control specialist for both ExoMars 2016 mission, including the Launch campaign in Baikonur (Kazakhstan) and ExoMars RSP mission, European side and system level
- Planetary Protection Expertise for TASI projects e.g. MSR ERO (Phase A/B1 Study and B2/CD/E1 proposal); SFR (Phase A Study); ExoMars RFM (preliminary studies, Maintenance and Schedule Protection and start of Phase B1/Advance B2); Mars Moon Lander
- Member of the former PP of Outer Solar Systems Working Group
- Member of former ECSS-U-ST-20C Working Group
- Instructor of the ESA Annual PP course since 2016
- Instructor of the PP course organized by COSPAR at CAST (China)
- Educator in the field of PP providing courses to people belong to and support ExoMars program in Italy and abroad since 2012

Contact email: diana.margheritis@thalesaleniaspace.com







Outline

- COSPAR PP Category III
- COSPAR PP Category IV
- Case study ExoMars
 - ExoMars 2016 PP Implementation
 - ExoMars Rover and Surface Platform PP implementation





Category III: Flyby and orbiter of missions to a target body for which there is a significant interest relative to the process of chemical evolution and/or origin of life and for which scientific opinion provides a significant² chance that contamination by the SCC can compromise future investigations

Applicability: Mars; Europa; Enceladus, others TBD

²Implies the presence of environments where terrestrial organisms could survive and replicate, and some likelihood of transfer to those places by a plausible mechanism



-Credit: NASA/JPL/Galileo











Category III- Description:

- Detailed documentation,
- Probability of Impact
- Use of cleanrooms during assembly and testing
- Possible bioburden reduction
- Possible organic inventory





-Credit: ESA/Mars Express



-Credit: NASA/JPL/Galileo



-Credit: NASA/JPL/Cassini







esa

Category IV: Lander of missions to a target body for which there is a significant interest relative to the process of chemical evolution and/or origin of life and for which scientific opinion provides a significant² chance that contamination by the SCC can compromise future investigations

Applicability: Mars; Europa; Enceladus, others TBD

Category IV **for Mars** is subdivided into Category IVa (basic reqs for all Mars surface missions), IV b (missions with life detection investigations), and IVc (missions accessing Mars special regions)



-Credit: ESA/Mars Express













Category IV – Description

For Mars Missions:

Category IVa:

- Lander systems not carrying instruments for investigation of Martian life and neither land nor access a Mars special regions (*)
- Are restricted to a surface bioburden level of $\leq 3 \times 10^5$ spores, and an average of ≤ 300 spores per square meter.

(*) Mars special region: Region within which terrestrial organisms are likely to replicate. Any region which is interpreted to have a high potential for the existence of extant Martian life forms [COSPAR Policy on Planetary Protection, approved by COSPAR Bureau on 3 June 2021)

 Analysis whether the SCC during nominal and off-nominal mission scenarios do not create a Mars special region in the local martian environment (e.g. SCC using radioisotope heat sources targeting areas with surface or sub-surface water ice)







Category IV – Description

Category IVb:

- Lander system carrying instruments for investigation of extant or extinct Martian life and neither land nor access a Mars special region. All of the requirements of Category IVa apply, along with the following requirement:
- The entire landed system is restricted to a surface bioburden level of $\leq 30(*)$ spores,

OR

- The <u>subsystems</u> which are involved in the acquisition, delivery, and analysis of samples used for life detection must be sterilized to levels of bioburden reduction driven by the nature and sensitivity of the particular life-detection experiments, and
- a method of <u>preventing recontamination</u> of the sterilized **subsystems** and the contamination of the **material to be analyzed** is in place.

(*) assumes 300 spores/m² cleanliness followed by process to reduce by 4 logs in viable organisms.

ThalesAlenia ^a Thales / Leonardo company





COSPAR Planetary Protection Categories

• Five Mission categories:

PLANET PRIORITIES	MISSION TYPE	MISSION CATEGORY	
Not of direct interest for understanding the process of chemical evolution. No protection of these planets is warranted.	Any	I	Ex. Flyby, Orbiter, Lander: Undifferentiated, metamorphosed asteroids; Io
Of significant interest relative to the process of chemical evolution and the origin of life, but only a remote chance that contamination by spacecraft could compromise future investigations.	Any	II	Ex: Flyby, Orbiter, Lander: Venus;Comets; Jupiter; Saturn; Uranus
Of significant interest relative to the process of chemical evolution and the origin of life and for which scientific opinion provides a	Flyby, Orbiter	ш	Ex: Flyby, Orbiters: Mars; Europa; Enceladus
significant chance of contamination which could compromise future investigations.	Lander, Probe	IV	Ex: Lander Missions: <mark>Mars</mark> ; Europa; Enceladus
Any Solar System Body	Earth Return « <u>restricted</u> » or «unrestricted»	v	Ex. Restricted: Mars; Europa Ex. Unrestricted: Venus, Moon





Space



Case Study – ExoMars

ExoMars project was a broad International Cooperation between ESA and Roscosmos with Instrument contributions from NASA. Two missions:

- ExoMars 2016 launched on March 2016
- ExoMars Rover and Surface Platform to be launched on 2022, cancelled





Case Study – ExoMars

ExoMars 2016: Category IVa

- lander system **not** carrying instruments for investigation of Martian life and ۲ neither land nor access a Mars special regions
- Planetary Protection Category III for the Trace Gas Orbiter (TGO)

ExoMars Rover and Surface Platform: Category IVb

lander system **carrying** instruments for investigation of extant or extinct Martian life and **neither land nor access** a Mars special regions















COSPAR Category IVa – Planetary Protection Implementation











Documentation Hierarchy









PP Management and Organization



• P-PPL define, manage and organize PP activities at all levels







PP Implementation

General requirements

- Management and documentation
- Organic material inventory (> 1Kg)
- 50 g org used > 25Kg , stored by customer for 50 year

Impact probability requirements

- Impact probability constraints for launcher upper stage
- Impact probability constraints for orbiter system
- by analysis

Bioburden requirements

- Bioburden allocation
- Bioburden reduction
- Cleanroom class
- Independent bioburden verification
- by tests/estimations











Impact Probability constraints

- 1. Launch Vehicle upper stage
 - The probability of impact on Mars by the Proton upper stage Breeze-M shall be $\leq 1x10^{-4}$ for the first 50 years after launch
- 2. <u>Trace Gas Orbiter:</u> One of the following conditions shall be met:



 The probability of impact on Mars by the SCC is
 ≤ 1x10⁻² for the first 20 years after launch, and

 \leq 5x10⁻² for the time period from 20 to 50 years after launch.

OR

 The total bioburden of the spacecraft, including surface, mated, and encapsulated bioburden, is < 5x10⁵ bacterial spores.







Impact Probability constraints

Approach



- Identification of those critical mission phases during which an unrecoverable SCC failure could lead to an unwanted impact (crash)
- Assess the probability of failure of those SCC systems potentially leading to an unwanted impact
- Consider additional effects due to micro meteoroids and space radiations
- Consider additional effects of human errors

Input data:

- Critical mission phases durations (based on Mission analysis trajectory data and parameters)
- Space environment, in particular: Radiation environment, Micrometeoroid environment
- Spacecraft Reliability Prediction Analysis or Fault Tree Analysis







Impact Probability constraints



The overall probability of crash on Mars was calculated as the sum of probabilities of crash due to different failure causes: failures generated by micrometeoroid impact, ground error, overheating, MSA and TGO failures

Probability of impact requirements can have an effect on the qualification of hardware (e.g., solar arrays for aerobraking), the trajectory design, the delta-v budget (re-targeting), and spacecraft design (e.g., location of tanks, additional micrometeoroid protection)

All activities necessary to perform a probability of impact analysis are interdisciplinary and require the interactions between different engineering disciplines!









- Exposed internal and external surface bioburden $\leq 3 \times 10^5$ bacterial spores
- Average surface bioburden density ≤ **300** bacterial spores/m²

(*)Total bioburden: surface, mated, and encapsulated







Bioburden Budgets

- Surface bioburden budget
 - To be within the surface bioburden constraints
 - allocated for all EDM elements
 - measured by bioburden assay procedures
- Encapsulated bioburden budget
 - No constraints; to be included in the total bioburden
 - allocated only for hard landing EDM elements
 - estimated/ measured by dedicated tests



AMARY 2048 . ROM Dro









Bioburden Budgets



- Surface bioburden budget: 538 lines

Encapsulated bioburden budget: 386 lines







- From bioburden budget: definition of
 - log-reduction to be achieved for each flight item
 - controlled environments class for Assembly, Test and Launch Operations
- Steps performed:
- 1. Bioburden assays of flight items
- 2. Sterilization of flight items
- 3. Integration of sterilized items in bioburden controlled environments
- 4. Environmental tests (at equipment, subsystem, module level)
- 5. Launch campaign: with bioburden controlled environments

Recontamination prevention and surface bioburden checks (including cleaning if necessary) in all the steps







Bioburden Assay Plan

- for each item before sterilization
- before closing not-accessible surfaces
- during AIT/AIV, Env.Test activities
- at launch site











Microbiological Laboratory

- Certified ExoMars Microbiological laboratory with certified personnel Choice of centralized activity at TAS-I Turin
- ESTEC (NL) Microbiological laboratory for EDM payloads









Requirement: Bioburden assays as per ECSS-Q-ST-70-55C tailored for ExoMars













Requirement: Sterilization as per ECSS-Q-ST-70-57C Dry Heat Microbial Reduction (DHMR)

- DHMR to reduce surface, mated and encapsulated spores -pending of the thermal cycle applied
- First evaluation of material and hardware <u>compatibility</u> with bioburden reduction procedures as per ECSS-Q-ST-70-53C
- Material, Part ,component and item compatibility with DHMR (incl. CTE) verification and qualification testing (e.g. 3 cycles)
- Preparation of Bioburden Reduction PLAN
- Bioburden assays before sterilization
- Sterilization T range: 110-125C
- 3-4 log reduction

alesAle







Sterilization processes

Bioburden reduction process	Followed by European Industries and Agency	
DHMR	ECSS-Q-ST-70-57C	
HYDROGEN PEROXIDE	NA	
UV RADIATION	NA	Ovens in Turin premises
GAMMA RADIATION	NA	



Oven in ESTEC premises (parachute)





Controlled environments for ExoMars

- Requirement: ISO 8 or better for flight HW assembly
- ISO 8 HC (*) for support
- ISO 7 HC and ISO 7 HC Portable Tent for EDM integration and opened EDM activities
- ISO 8 with precautions for TGO integration, launch stack assembly, fairing

(*) HC Highly Controlled = spores measured on cleanroom surfaces and airborne

ISO 14644 – 1(1999): Classification of air cleanliness ECSS-Q-ST-70-58C (2008): Bioburden control of cleanrooms















Training Program

- Level 1: project team, sub-contractors and instrument providers
- Level 2: all personnel working in bioburden controlled environments
- Level 3: supervisors



More than 300 people trained during ExoMars 2016 Mission







Recontamination prevention

- Continuous bioburden monitoring
- Dedicated and cleaned transport containers
- Dedicated approach for GSE and tools
- Venting box in EDM backshell; Bioseal

















Recontamination prevention

- Use of sterile consumables: IPA 70%, wipes, covers/biobarriers/ packaging material, fluids
- Garments: decontaminated undergarments, bunny suit and hood; sterile mask and gloves



During environmental tests and launch campaign







Recontamination prevention

- external surfaces ≤ 1000 sp/m2 verified pre-launch in order to avoid EDM recontamination during the launch (req implemented by the Prime)
- External TGO MLIs DHMR processed









COSPAR Category IVb – Planetary Protection Implementation











PP Management and Organization

- Lavochkin (LAV), Prime of the Russian industries
 - developer of the Russian Descent Module (DM)
 - Responsible for SCC AIT and associated PP implementation

- Thales Alenia Space Italia (TAS-I), Prime of the European industries
 - developer of European mission elements and associated PP implementation
 - responsible or the Spacecraft Composite (SCC) requirements and design







PP Management and Organization









PP Requirements

- General
- Impact probability
- Bioburden
- Mars samples contamination requirements







PP Requirements – Impact probability

1. <u>Launcher upper stage</u>: The probability of impact on Mars of the launcher upper stage shall be

 \leq 1x10⁻⁴ for the first 50 years after launch

2. <u>Spacecraft:</u> The probability of impact on Mars by the SCC, including CM-DMC separation, shall be

 $\leq 1 \times 10^{-2}$







PP Requirements – Bioburden – Bacterial spores Spacecraft ≤ 500.000 (*) (Total)

with

Descent Module ≤ 300.000 (*) (surface bacterial spores on exposed internal and external surfaces)

Rover Module ≤ 20.000 (surface bacterial spores on exposed internal and external surfaces)

and

Average surface bioburden density on DM and RM \leq 300 bacterial spores/m² on exposed internal and external surfaces.

(*) including 20% ESA Project margin)







PP Requirements – Bioburden – Bacterial spores

Average surface bioburden on the RM subsystems <u>involved in the</u> <u>acquisition, delivery, and analysis of martian samples for life detection</u> shall be ≤ 0.03 bacterial spores/m²









PP Requirements – Mars Sample Contamination Requirement

The maximum terrestrial organic contamination level per substance class and per gram of Martian samples for life detection shall be:

Substance class	Contamination level per gram of
	martian sample delivered for life
	detection
Material from biological sources	≤ 50 *10 ⁻⁹ gram
Monomers of Kapton, Mylar and PTFE	≤ 500 *10 ⁻⁹ gram
Fluorinated technical lubricants	≤ 500 *10 ⁻⁹ gram
Any other organic compound	≤ 50 *10 ⁻⁹ gram







PP Implementation – Bioburden

1. 500,000 spores allocation (including the recontamination during the launch campaign):

Module	Surface bioburden at delivery	Total bioburden at delivery	Surface bioburden at launch	Total bioburden at launch	
	[spores]	[spores]	[spores]	[spores]	
SCC	#	400000	#	500000	
СМ	#	40000	#	40000	
DMC	170000	360000	270000	460000	
DM	150000	340000	250000	440000	
RM	20000	#	20000	#	

2. Preparation of the SCC bioburden budget which includes the DM, RM, CM bioburden budgets plus recontamination during ATLO

CM budget prepared taking into account the outputs of the CM BuBu analysis







PP Implementation – Bioburden

- Break-up/burn-up (BuBu) of the CM entering the Martian atmosphere is used to claim bioburden reduction if the conditions of 500° C for ≥ 0.5 seconds are reached
- CM Bubu analysis includes the consolidated CM design and final landing parameters
 - CM bioburden budget to be prepared taking into account BuBu outputs
 - Identification of the CM elements to be sterilized / bioburden densities



CM external surfaces ≤ 1000 sp/m2 (MLIs DHMR processed) to avoid DM recontamination during the launch (req implemented by the Prime)







PP Implementation – General approach

- Flow down of customer PP requirements into Project System Level PP requirements document (Prime PP requirements doc.)
- Flow down of Prime PP requirements into equipments/subsystems spec., subcontractors spec. and all system level **specifications**.
- Issue of PP Plan including PP documentation to be released by the Prime with the related reviews
- Flow down of Prime PP requirements into DM-CM, DM-RM, LV-SCC, RM-Payloads IRDs
- From bioburden budgets→ definition of log-reductions (items) and ATLO controlled environments
- Recontamination prevention and surface bioburden checks (including cleaning if necessary)







Requirement: Bioburden assays as per ECSS-Q-ST-70-55C tailored for ExoMars

• Several certified Microbiological Laboratories with certified personnel in:

TASinI Turin (IT),

ADS Stevenage (UK),

OHB Bremen (GE),

IBMP (Ru),

ESTEC (NL),

Bioclin (F),

NASA (USA)











Sterilization processes



Bioburden reduction process	Followed by European Industries and Agency	Followed by LAV	
DHMR	ECSS-Q-ST-70-57C	ECSS-Q-ST-70-57C	
HYDROGEN PEROXIDE	ECSS-Q-ST-70-56C	NA	
UV RADIATION	NA	LAV procedures	
GAMMARADIATION	NA	LAV procedures	

- All the flight hardware to be sterilized has to be **compatible** with the selected sterilization process
- ECSS-Q-ST-70-53C used to evaluate material and hardware compatibility with bioburden reduction procedures





Controlled Environments

- Requirement: ISO 8 or better for flight HW assembly
- ISO 7 HC for DM (TASinI), RM (ADS, TASinI), ALD/Drill except UCZ (TASinI) integration



- ISO 7 HC portable Tent for opened DM and RM activities
- ISO 8 HC (support)
- ISO 8 (with precautions) for CM integration (OHB), launch stack assembly, fairing (Cosmodrome Baikonur)
- ISO 5 HC for transport and aseptic operations (TASinI)
- ISO 3 sterile AMC-controlled wrt sel. organics for UCZ ALD integration (TASinI)









PP Implementation – Bioburden and Mars Sample Contamination Requirement

Identification of RM Ultra Clean Zone (UCZ) or contamination controlled RM volume and surfaces in contact with Martian samples when collected, processed and analyzed







PP Implementation – Mars Sample Contamination Requirement

- RM flight H/W parts on the Mars sample path or UCZ parts
 - Disassembled, cleaned and packed (in ISO 5 env.) with high performance techniques;
 - 4-log sterilization to achieve 0.03 bacterial spores/m2
 - Transportation to the GBT into an sterile environment ISO 5 w/o breaking sterilization chain









PP Implementation – Mars Sample Contamination Requirement

- RM flight H/W parts on the Mars sample path or UCZ parts
 - Ultracleaning and UCZ AIT in sterile environment to preserve item's sterility.
 - UCZ closure and overpressurization with dedicated FGSE





 Bottom-up approach is used to derive the contamination of the Martian sample at the End of life sample as a sum of the different contributions (UCZ surface and airbone contamination, Drill tool chamber contamination and RM external surfaces off-gassing)







PP Documentation and Reviews

Title	Preliminary	Final	PPAA Approval/R eview	EXM 2016	EXM 2022	
PP Requirements	PRR	SRR	А	Y	Y	Set of PP reqs
PP Plan	SRR	PDR	A	Y	Y	Primary planning describing how the project meets the PP reqs
PP Implementation Plan	PDR	CDR	R	Y	Y	Provide information about the detailed implementation of the PP reqs in line with the PPP
Pre-Launch PP Report	FAR	FRR	R	Y	Y	To demonstrate the project meets the PP reqs, in particular bioburden allocations
Post-Launch PP Report		No later than 6 months after launch	R	Y	TBW	To account for effects of events from submission of the Pre-launch PP report
Extended Mission PP Report		Before the commitment for the extended mission	R	NA		To provide evidence of continuing compliance with PP reqs considering the activities of the extended mission phase
End-of-Mission PP Report		No later than 6 months after end- of-mission	R	TBW	TBW	To describe the degree to which the project meets the PP reqs throughout the complete mission
Organic Materials Inventory	CDR	FRR	R	Y	Y	To document the org. material on the spacecraft

• PRR: preliminary requirement review; SRR: system requirement review; PDR: preliminary design review; CDR: critical design review; FAR: final acceptance review; FRR: flight readiness review







PP Documentation and Reviews

 Implementation of PP requirements is not limited to PP documents but need to be reflected in the affected project documentation e.g. system requirements specification, quality plan, AIT and AIV plan, VCD

NCR related to PP are always major







Thanks for your attention!

Questions?





